

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 (Previously Presented). Wall with a set of doors for closing off a bay (3) in this wall (4), comprising a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement, a slit (31) being provided between the wall (4) and the rigid bottom edge (17) of the second door (2) as this second door is moved upwards into the open position, the flexible door (1) at least partially being arranged between said second door (2) and said wall (4), wherein the flexible door (1) is movable through the slit (3) between its open position and its closed position when the second door (2) is in the open position, wherein the flexible door is supported against the bottom edge (17) of the second door (2) when this second door (2) is in the open position and the flexible door (1) is in its closed position.

2 (Previously Presented). Wall with a set of doors as claimed in claim 1, wherein the flexible door is in contact

with the wall (4) above the bay (3) to form a seal between the wall (4) and the flexible door (1) and wherein the flexible door is supported against the bottom edge (17) of the second door (2) in order to maintain said contact and to maintain said seal when said second door (2) is in the open position and said flexible door (1) is in its closed position.

3 (Previously Presented). Wall with a set of doors as claimed in claims 1 or 2, wherein the flexible door (1) has a sealing element (26) extending across substantially the entire width of the flexible door (1), which sealing element extends between this door (1) and a part of the wall (4) located above the bay (3), the sealing element forming a seal between the wall (4) and the flexible door (1) when the flexible door (1) is in the closed position.

4 (Previously Presented). Wall with a set of doors as claimed in claim 1, wherein the flexible door has a sealing element (26) extending along substantially the entire width of the flexible door (1) which extends between this door (1) and the bottom edge (17) of the second door (2) so that the flexible door (1) is clamped between the wall (4) and this bottom edge (17) when the flexible door is in the closed position.

5 (Withdrawn). Wall with a set of doors as claimed in claim 3, characterised in that the sealing element (26) is a flap (27) which extends between the wall (4) and the flexible door (1) when the flexible door (1) is in the closed position.

6 (Previously Presented). Wall with a set of doors as claimed in claim 3, wherein the sealing element (26) is a thickened section (28) of an elastic material, the sealing element being clamped between the wall (4) and the bottom edge (17) of the second door (2) when the second door is in the open position and when said flexible door (1) is in its closed position.

7 (Previously Presented). Wall with a set of doors as claimed in claim 1, wherein, when said second door (2) is in the open position, as said flexible door (1) is displaced towards its closed position or towards its open position, the flexible door is supported against a guide surface on the wall (4) above the bay (3) or on the bottom edge (17) of the second door (2).

8 (Previously Presented). Wall with a set of doors as claimed in claim 7, characterised in that the bottom edge (17) of the second door (2) is provided with said guide surface (25), such that the flexible door slides on this edge (17) as the flexible door is moved upwards or downwards.

9 (Previously Presented). Wall with a set of doors as claimed in claims 7 or 8, wherein a part of the wall (4) located above the bay (3) has said guide surface (25) such that the flexible door (1) slides relative to this wall (4) as it is moved upwards or downwards.

10 (Previously Presented). Wall with a set of doors as claimed in claim 8, wherein the guide surface comprises at least one cylinder (25) with an axis which extends substantially transversely to the direction of displacement of the flexible door (1) as it is moved downwards or upwards.

11 (Previously Presented). Wall with a set of doors as claimed in claim 1, wherein the flexible door (1) comprises a shutter (9) with side edges (7, 8) that are guided relative to guide tracks (5, 6) passing through said slit

between the wall (4) and the bottom edge (17) of the second door (2).

12 (Previously Presented). Wall with a set of doors as claimed in claim 11, wherein said guide tracks (5, 6) extend at least partially in the bay (3) or at the side of the bay that is directed towards the second door (2).

13 (Previously Presented). Wall with a set of doors as claimed in claim 11 or 12, characterised in that the guide tracks (5, 6) are elastically or pivotably mounted to the wall (4).

14 (Previously Presented). Wall with a set of doors as claimed in claim 11, characterised in that the guide tracks (5, 6) constitute seals between the wall (4) and said second door (2) when the latter is in the closed position.

15 (Currently Amended). Wall with a set of doors for closing off a bay (3) in this wall (4), comprising a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement, a

slit (31) being provided between the wall (4) and the rigid bottom edge (17) of the second door (2) as this second door is moved upwards into the open position, the flexible door (1) at least partially being arranged between said second door (2) and said wall (4), wherein the flexible door (1) is movable through the slit (3) between its open position and its closed position when the second door (2) is in the open position, wherein the flexible door is supported during its displacement ~~against a guide surface provided on the wall (4) above the bay (3) or~~ on the bottom edge (17) of the second door (2) when this second door (2) is in the open position and said flexible door (1) is displaced towards its closed position or towards its open position.

16 (Previously Presented). Wall with a set of doors as claimed in claim 15, wherein said guide surface (25) is provided on the bottom edge (17) of the second door (2) whereby the flexible door (2) slides on this bottom edge (17) as it is moved upwards or downwards.

17 (Previously Presented). Wall with a set of doors as claimed in claims 15 or 16, wherein said guide surface (25) is provided on the wall (4) above the bay (3)

enabling the flexible door (1) to slide relative to this wall (4) as it is moved upwards or downwards.

18 (Currently Amended). Set of doors for closing off a bay (3) in a wall (4), comprising a first flexible door (1) and a second door (2) having at least a rigid bottom edge (17), each of these doors being movable between an open position and a closed position through, respectively, an upward movement and a downward movement, the flexible door having driving means, comprising a drum, that are mounted above the second door, wherein the flexible door is supported against the bottom edge (17) of the second door (2) when this second door (2) is in the open position and the flexible door (1) is in its closed position.

19 (Previously Presented). Set of doors as claimed in claim 18, wherein the flexible door (1) has a sealing element (26) extending across substantially the entire width of the flexible door (1) for forming a seal between the wall (4) and the flexible door (1) when the flexible door (1) is in the closed position.

20 (Previously Presented). Set of doors as claimed in claim 18, wherein the flexible door has a sealing element

(26) extending along substantially the entire width of the flexible door (1) between the flexible door (1) and the bottom edge (17) of the second door (2) when the flexible door is in the closed position and the second door is in its open position.

21 (Previously Presented). Set of doors as claimed in claim 19 or 20, wherein the sealing element (26) is a thickened section (28) of the flexible door.

22 (Previously Presented). Set of doors as claimed in claim 18, wherein, when said second door (2) is in the open position, as said flexible door (1) is displaced towards its closed position or towards its open position, the flexible door is supported against a guide surface on the bottom edge (17) of the second door (2).

23 (Previously Presented). Set of doors as claimed in claim 22, wherein said guide surface (25) is provided on the bottom edge (17) of the second door (2) such that the flexible door slides on this edge (17) as the flexible door is moved upwards or downwards when the second door is in its open position.



24 (Previously Presented). Set of doors as claimed in claim 22 or 23, wherein the guide surface comprises at least one cylinder (25) with an axis extending substantially transversely to the direction of displacement of the flexible door (1) as is moved downwards or upwards.

25 (New). Set of doors as claimed in claim 18 wherein the flexible door is supported during its displacement against a guide surface provided on the wall (4) above the bay (3) when said second door (2) is in the open position and said flexible door (1) is displaced towards its closed position or towards its open position.